

**METALLIX**  
**100% SOLIDS**  
**METALLIC EPOXY COATING**  
 LEAVE THE ORDINARY BEHIND  
**MATERIAL SAFETY DATA SHEET**

PRODUCT CODE: MET A

**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: METALLIX - 100% Solids Epoxy Metallic Colorcoat  
 PRODUCT CODES: MET Part A

MANUFACTURER: Original Color Chips Co  
 STREET ADDRESS: 26200 Groesbeck Hwy  
 CITY, STATE, ZIP: Warren, MI 48089

INFORMATION PHONE: 724-483-9300  
 EMERGENCY PHONE: Chemtrec  
 800-424-9300 FAX PHONE: 724-483-9306

PREPARED BY: Harry

Jackson DATE REVISED:

**SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**  
 9/14/05

INGREDIENT	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	WEIGHT %
MODIFIED DIGLYCIDYL ETHER OF BIPHENOL A	25068-38-6	NONE	NONE	NONE	
ALKYL GLYCIDYL ETHER	68609-97-2	NONE	NONE	NONE	
FLUROALIPHATIC POLYMERIC ESTERS (LESS THAN 0.3%)	UNKNOWN	NONE	NONE	NONE	
1,2-PROPANEDIOL	57-55-6	NONE	NONE	NONE	
PROPRIETARY NON-HAZARDOUS ADDITIVES	N/A	NONE	NONE	NONE	
AMORPHOUS SILICA	7631-86-9	80mg/m3	10mg/m3	NONE	
NONYL PHENOL	25154-52-3	NONE	NONE	NONE	
BENZYL ALCOHOL	100-51-6	NONE	NONE	NONE	

SECTION 2 NOTES:

\*\*\*No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.\*\*\*

**SECTION 3: PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE AND ODOR: LOW VISCOSITY LIQUID - AMBER  
 CLEAR BOILING POINT OR RANGE: 200 TO 560 o F:  
 VAPOR DENSITY (AIR = 1): N/A  
 SPECIFIC GRAVITY (H2O = 1):  
 1.1 EVAPORATION RATE: N/A  
 SOLUBILITY IN WATER: NEGLIGIBLE

SECTION 3 NOTES:

**SECTION 4: FIRE-FIGHTING MEASURES**

FLAMMABLE LIMITS IN AIR, (% by volume) UPPER: N/A  
 LOWER: N/A

FLASH POINT: 200 + F

METHOD USED: SETA FLASH

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES: DO NOT ENTER CONFINED FIRE AREA WITHOUT FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS, COOL ALL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS: NO UNUSUAL FIRE HAZARDS KNOWN.

**METALLIX**  
**100% SOLIDS**  
**METALLIC EPOXY COATING**  
**LEAVE THE ORDINARY BEHIND**  
**MATERIAL SAFETY DATA SHEET**

PRODUCT CODE: MET A

**SECTION 5: STABILITY AND**

**REACTIVITY STABILITY:** STABLE  
**CONDITIONS TO AVOID (STABILITY):** AVOID EXCESSIVE HEAT OR OPEN FLAMES.

**INCOMPATIBILITY (MATERIAL TO AVOID):** CAN REACT VIGOROUSLY WITH STRONG OXIDIZING AGENTS AND STRONG LEWIS ACIDS OR MINERAL ACIDS.

**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** CO<sub>2</sub>, ALDEHYDES, ACIDS. REACTION WITH SOME CURING AGENTS CAN GENERATE LARGE AMOUNTS OF HEAT.

---

**HAZARDOUS POLYMERIZATION:** WILL NOT

---

OCCUR **SECTION 6: HAZARDS IDENTIFICATION**

**HMS HAZARD CLASSIFICATION**

**HEALTH:** 2      **FLAMMIBILITY:** 1      **REACTIVITY:** 0      **PERSONAL PROTECTIVE EQUIPMENT:** G

**POTENTIAL HEALTH EFFECTS**

**EYES:** MAY CAUSE IRRITATION BUT NO CORNEAL INJURY IS LIKELY.

**SKIN:** MAY CAUSE IRRITATION OR ALLERGIC SKIN RESPONSE.

**INGESTION:** THIS MATERIAL HAS A PROBABLE LOW ACUTE ORAL

---

**INHALATION:** NO GUIDE FOR CONTROL KNOWN, HOWEVER, EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION TO ~~TOXIC~~ NOSE, THROAT OR MUCOUS MEMBRANES.

---

**HEALTH HAZARDS (ACUTE AND CHRONIC):** EPOXY RESINS CAN CAUSE SENSITIZATION BY EXPOSURE THROUGH CONTACT OR HIGH CONCENTRATIONS OF VAPOR. EYES: INJURY IS UNLIKELY BUT STAIN FOR EVIDENCE OF CORNEAL INJURY.

**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:** RESPIRATORY CONDITIONS OR OTHER ALLERGIC RESPONSE.

**CARCINOGENICITY**

OSHA: NO      NTP: NO      IARC: NO  
NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

**SECTION 7: FIRST AID MEASURES**

**EYES:** FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES AND CONSULT A PHYSICIAN.

**SKIN:** SKIN CONTACT WILL NORMALLY CAUSE NO MORE THAN IRRITATION BUT WASH AFFECTED AREA WITH SOAP AND WATER AND REMOVE CONTAMINATED CLOTHING PROMPTLY.

**INGESTION:** LOW IN TOXICITY, INDUCE VOMITING ONLY IF LARGE AMOUNTS OF MATERIAL ARE INGESTED, OTHERWISE DO NOT INDUCE VOMITING AND CONSULT A PHYSICIAN.

**INHALATION:** REMOVE VICTIM TO FRESH AIR AREA AND ADMINISTER OXYGEN IF NECESSARY. CONSULT PHYSICIAN IF NECESSARY.

---

**SECTION 8: RELEASE MEASURES**

---

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

WEAR RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF THE SOURCE AT THE LEAK. REMOVE EXCESS WITH VACUUM TRUCK AND TAKE UP THE REMAINDER WITH AN ABSORBANT SUCH AS CLAY AND PLACE IN DISPOSAL CONTAINERS. FLUSH AREA WITH WATER TO REMOVE RESIDUE.

SECTION 8 NOTES:



PRODUCT CODE: MET A

**SECTION 9: WASTE DISPOSAL**

**WASTE DISPOSAL METHOD:** DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS.

**SECTION 10: HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:**

STORE IN COOL DRY PLACE. SEAL ALL PARTIALLY USED CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFOR, READ THE MSDS'S OF ALL THE COMPONENTS PRIOR TO USING MATERIAL. PROPERLY LABEL ALL CONTAINERS.

**OTHER PRECAUTIONS:**

~~AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS GENERATED FROM THE MATERIAL. OBSERVE CONDITIONS OF GOOD GENERAL HYGIENE AND SAFE WORKING PRACTICES. CONTAMINATED LEATHER ARTICLES CANNOT BE CLEANED AND MUST BE DISCARDED IF CONTAMINATED WITH THIS PRODUCT. WASH ALL CONTAMINATED CLOTHING PRIOR TO THE REUSE THEREOF.~~

**SECTION 10 NOTES:**

**SECTION 11: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**RESPIRATORY PROTECTION:**

USE A NIOSH APPROVED RESPIRATOR AS REQUIRED TO PREVENT OVER-EXPOSURE TO VAPOR IN ACCORDANCE WITH 29 CFR 1910.134. GENERAL EXHAUST IS USUALLY SUFFICIENT IN LIEU OF NIOSH RESPIRATOR.

**VENTILATION:**

GENERAL EXHAUST IS USUALLY SUFFICIENT TO CONTROL VAPORS AND EXPOSURE HAZARDS.

**PROTECTIVE GLOVES:**

IMPERVIOUS GLOVES - NEOPRENE OR RUBBER

**EYE PROTECTION:**

~~SPLASH GOGGLES OR GLASSES WITH SIDE SHIELDS.~~

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**

WEAR BODY COVERING CLOTHING AND OTHER COVERING AS NECESSARY SUCH AS APRON AND APPROPRIATE FOOTWEAR TO AVOID CONTACT WITH MATERIAL.

**WORK HYGIENIC PRACTICES:**

OBSERVE GOOD GENERAL HYGIENIC PRACTICES.

**SECTION 12: DISCLAIMER**

**DISCLAIMER:** THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE AND IS BELIEVED TO BE ACCURATE, HOWEVER, THE MANUFACTURER MAKES NO WARRANTY EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS OBTAINED FROM THE USE THEREOF. ACCORDINGLY, WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THIS PRODUCT.



PRODUCT CODE: MET B

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: METALLIX - 100% Solids Epoxy Metallic Colorcoat  
PRODUCT CODES: MET Part B

MANUFACTURER: Original Color Chips Co  
STREET ADDRESS: 26200 Groesbeck Hwy  
CITY, STATE, ZIP: Warren, MI 48089

INFORMATION PHONE: 724-483-9300  
EMERGENCY PHONE: Chemtrec 800-424-9300  
FAX PHONE: 724-483-9306

PREPARED BY: Harry Jackson

DATE REVISED: 9/14/05

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	WEIGHT %
BENZYL ALCOHOL	100-51-6	NONE	NONE	NONE	
3-AMINOMETHYL-3,5,5-TRIMETHYL CYCLOHEXANE	2855-13-2	NONE	NONE	NONE	
2-HYDROXYBENZOIC ACID	69-72-7	NONE	NONE	NONE	

SECTION 2 NOTES:

\*\*\*No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present.\*\*\*

SECTION 3: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: AMBER CLEAR LIQUID WITH AMINE

ODOR BOILING POINT OR RANGE: 401o F:

VAPOR DENSITY (AIR = 1): N/A

SPECIFIC GRAVITY (H2O = 1):

1.0 EVAPORATION RATE: N/A

SOLUBILITY IN WATER: NEGLIGIBLE

SECTION 3 NOTES:

SECTION 4: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: N/A  
(% by volume) LOWER: N/A

FLASH POINT: 200+F

METHOD USED: SETA FLASH

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, WATER FOG

SPECIAL FIRE FIGHTING PROCEDURES: TOXIC FUMES WILL BE EVOLVED WHEN THIS MATERIAL IS INVOLVED IN A FIRE. A SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FIRE FIGHTERS. COOL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN



PRODUCT CODE: MET B

**SECTION 5: STABILITY AND REACTIVITY**

**MATERIAL SAFETY DATA SHEET**

STABILITY: STABLE

CONDITIONS TO AVOID:

AVOID CONTACT WITH OPEN FLAMES AND ALL SOURCES OF IGNITIONS AND SPARKS.

INCOMPATIBILITY (MATERIAL TO AVOID):

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, MINERAL ACIDS AND EPOXY RESINS IN UNCONTROLLED AMOUNTS.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: CO, CO<sub>2</sub>, NOX

HAZARDOUS POLYMERIZATION: WILL NOT

---

OCCUR **SECTION 6: HAZARDS IDENTIFICATION**

HMIS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMIBILITY: 1 REACTIVITY: 0 PERSONAL PROTECTIVE EQUIPMENT: G

POTENTIAL HEALTH EFFECTS

EYES: WILL CAUSE BURNS TO THE EYES. HIGH VAPOR CONCENTRATIONS CAN CAUSE SEVERE IRRITATION TO THE

EYES. SKIN: WILL CAUSE BURNS TO THE SKIN

INGESTION: LIQUID CAN CAUSE SEVERE DAMAGE TO MUCOUS MEMBRANES IF SWALLOWED.

---

INHALATION: HIGH CONCENTRATIONS OF VAPOR CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT, NAUSEA AND DIZZINESS.

---

HEALTH HAZARDS (ACUTE AND CHRONIC): PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSES.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: RESPIRATORY CONDITIONS OR OTHER ALLERGIC AILMENTS

CARCINOGENICITY

OSHA: NO NTP: NO IARC: NO  
NO LISTED INGREDIENTS OF THIS PRODUCT ARE REGULATED AS CARCINOGENS.

**SECTION 7: FIRST AID MEASURES**

EYES:

IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE LIFTING UPPER AND LOWER LIDS. GET IMMEDIATE MEDICAL ASSISTANCE.

SKIN:

FLUSH SKIN WITH WATER FOR AT LEAST 15 MINUTES AND REMOVE ALL CONTAMINATED CLOTHING IMMEDIATELY. GET MEDICAL ATTENTION IF REDDENING OR SWELLING OCCURS.

INGESTION:

DO NOT INDUCE VOMITING. DILUTE BY GIVING WATER OR MILK TO DRINK IF VICTIM IS CONSCIOUS. GET MEDICAL ATTENTION IMMEDIATELY.

---

INHALATION:

REMOVE TO FRESH AIR IF EFFECTS PERSIST AND ADMINISTER OXYGEN IF NECESSARY.

---

**SECTION 8: RELEASE MEASURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

AVOID CONTACT WITH MATERIAL. WEAR THE APPROPRIATE SAFETY EQUIPMENT. STOP SPILL AT SOURCE, DYKE AREA TO PREVENT SPREADING. PUMP LIQUID TO SALVAGE TANK. TAKE UP REMAINDER WITH CLAY OR OTHER ABSORBANT AND PLACE IN DISPOSAL CONTAINERS.



PRODUCT CODE: MET B

**SECTION 9: WASTE DISPOSAL**

**MATERIAL SAFETY DATA SHEET**

**WASTE DISPOSAL METHOD:**

DISPOSE OF MATERIAL AS A HAZARDOUS WASTE ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS

**SECTION 10: HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:**

AVOID ALL SKIN CONTACT. AVOID BREATHING VAPORS. RESEAL PARTIALLY USED CONTAINERS. PROPERLY LABEL ALL CONTAINERS. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICES.

**OTHER PRECAUTIONS:**

---

MIXED MATERIALS CONTAIN THE HAZARDS OF ALL THE COMPONENTS, THEREFORE, READ THE MSDS OF ALL COMPONENTS TO BECOME FAMILIAR WITH ALL HAZARDS PRIOR TO USING THIS PRODUCT.

---

**SECTION 11: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**RESPIRATORY PROTECTION:**

---

NIOSH APPROVED RESPIRATOR PROTECTION REQUIRED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROLS. FOR EMERGENCIES A SELF-CONTAINED BREATHING APPARATUS OR A FULL FACE RESPIRATOR IS RECOMMENDED.

---

**VENTILATION:**

AVOID BREATHING VAPORS, VENTILATION MUST BE SUFFICIENT TO CONTROL VAPORS.

**PROTECTIVE GLOVES:**

IMPERVIOUS GLOVES, NEOPRENE OR RUBBER.

**EYE PROTECTION:**

---

SPLASH PROOF GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS.

---

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:**

CLEAN BODY COVERING CLOTHING AS WELL AS APRON FOOTWEAR OR OTHER EQUIPMENT SHOULD BE USED AS DEEMED NECESSARY TO AVOID CONTACT WITH THE MATERIAL.

**WORK HYGIENIC PRACTICES:**

OBSERVE GENERAL GOOD HYGIENIC PRACTICES.

**SECTION 12: DISCLAIMER**

**DISCLAIMER:** THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE AND IS BELIEVED TO BE ACCURATE, HOWEVER, THE MANUFACTURER MAKES NO WARRANTY EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS OBTAINED FROM THE USE THEREOF. ACCORDINGLY, WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THIS PRODUCT.

---

---